

BASIC ROUTER FEATURES

- Industrial robust design and compact metal housing
- High data speed via 4G LTE
- Strong electromagnetic interference resistance, heat endurance and radiation ability
- Supports multiple VPN (IPSec, OpenVPN, VPN Client, GRE, etc.)
- Supports multiple network protocols (ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS, etc.)
- Supports multiple functions (DHCP, DNS, DDNS, Firewall, NAT, DMZ host, etc.)
- Built-in watch dog, multi-link detection ensures working in stable and secure way

(((●))) WTWIRELESS

6200 SERIES

- Network failover and failback via Wi-Fi & Wired Internet
- Wi-Fi Built-In, Optional: Wi-Fi Antenna required
- 2xLAN or 1xLAN + 1xWAN
- WAN port support PPPoE, static IP, DHCP client, 4G
- Always online, automatic reboot if disconnected to ensure continual connection
- LCP/ICMP/flow/heartbeat check, to ensure network usability
- Web/CLI/SSH/management platform support, easy to configure
- SNMP network management, NTP support
- Local & remote management (configuration, status, upgrade firmware, ping, reboot)
- Supports Port forwarding and Bridge
- Supports timing operation
- Supports LED status indication
- Shock and vibration resistant
- Control by SMS, email
- Schedule reboot

rev. 6/1/2021

(800) 475-1001



SPECIFICATIONS

Module:	Quectel EP06-A	
Category:	Cat-6	
Carrier Approvals:	Verizon, AT&T,	
	T-Mobile	
Regulatory Approvals:	FCC/IC, PTCRB, GCF	
Frequency Bands:	B2,B4,B5,B7,B12,B13	
	B25,B26,B29,B30,B66	
Peak Data Speeds LTE:	DL 300 Mbps/ UL 50 Mbps	

Interface Type:	2x 1 Gbps ports (RJ45) LED: "WLAN," "WAN," "LAN," "NET" 2 x SMA-K antenna interface 2 x RP-SMA Wi-Fi interface SIM/UIM: 1.8V/3V Power: "PWR" 5V ~ 30V Reset: "RST"	SIM: Dimensions:	2FF Item (L x W x H): 4 x 2.9 x 1 inch Packaging (L x W x H): 8.6 x 4.7 x 3 inch Item Weight: 0.5 lbs. Packaging: 1.5 lbs. total weight including product
Power Adapter:	Certificate: FCC, UL	Certificates:	FCC, ISO, CE, RoHS
Power Consumption: Physical:	Idle: <45mA@12VDC Data: <300mA@12VDC Average: 150mA@12VDC Operating Temperature	Package Content:	6200 - 2 Port Router CAT5 Ethernet Cable Power Adapter 2 x Cellular Antenna - Mag Mount
i nysicai.	Storage: -40°C to 85°C Working: -30°C to 75°C Humidity: 95% maximum	Wi-Fi:	1 SIM Optional Feature, must have
	(non-condensing)		Ŵi-Fi antenna

rev. 6/1/2021

(800) 475-1001

sales@WTIwireless.com

A A Charles and a constraint of the second s